

TRAY BLAST CHILLERS INFINITY



CHARACTERISTICS AND FUNCTIONS

- Circulation of air inside the cell
- Structure of the unit in AISI 304 stainless steel
- External finish in Scotch-brite satin
- Isolated with high density polyurethane foam (43kg/m³)
- Adjustable stainless steel feet
- Cells with rounded internal corners
- Rack and guides for holding easily removable and individually washable 60X40 trays.
- Door with spring return and removable magnetic seal
- Fan block system when door is open
- Easy access to the evaporator unit for easy cleaning
- Temperature probe with internal heating
- Conforms to HACCP
- Waste drain

OPTIONAL

- Pair of tray guides INOX blast chillers 4060
- Antibacterial lamp kit
- Temperature probe with internal heating
- USB kit
- 60x40 Stainless steel grid without stop
- 2+2 wheel kit diameter 80 in stainless steel
- Blast chiller filter
- Cooling by water unit

BLAST CHILLERS																		
Number of doors																		
Width (mm)																		
Depth (mm)																		
Height (mm)																		
Temperature range																		
Kg of product per cycle from +90° to + 3°in 90 minutes																		
Kg of product per cycle from +90° to - 18°in 240 minutes																		
Freezing capacity in Kgs/h from +30°C to -18°C to the heart																		
Capacity of pairs of tray guides																		
Power supply																		
Defrosting																		
Number of pairs of tray guides																		
Weight (Kg)																		
dbA																		
Absorbed Power (kW)																		
Absorption (A)																		
Refrigerating Power (kW)																		
Installed rated Power (HP)																		
Infinity 5T	1	784	800	900	-18°C / +90°C	20	15	7	6	230/1/50+N	HOT GAS	5	125	58	1,05	5	0,95	1
Infinity 10T		800	825	1800		40	30	15	15	400/3/50+N		10	190	68	2,5	4,4	2,08	1,8
Infinity 15T		800	825	2025		55	40	21	19	400/3/50+N		15	220	69	3,0	4,4	2,43	2



