

FOOD STORAGE CABINETS



FEATURES

- Stainless steel structure with outer finish in scotch-brite satin or PPS with internal surfaces in aluminium
- Isolated with 75mm of high density polyurethane foam (43kg/m³)
- Adjustable feet in plastic/stainless steel (h120-150)
- Newly designed grid supports in ABS
- Rounded internal corners to facilitate cleaning
- Automatic defrosting and evaporation of condensed water
- Patented single-piece refrigeration unit
- Refrigeration unit adapted for use in tropical conditions (high performance in environments up to 43°C)
- Optimisation of internal and external air flows
- Fan block when door is open

	TN 700 INOX	TN 700 PPS AL	BT 700 INOX	BT 700 PPS AL	TN 1400 INOX	TN 1400 PPS AL	BT 1400 INOX	BT 1400 PPS AL
Energy class	B	B	D	D	D	D	D	D
Number of doors	1				2			
Width (mm)	770				1540			
Depth (mm)	822							
Height (mm)	2025							
Temperature range	-2° C / +8° C		-20° C / -10° C		-2° C / +8° C		-20° C / -10° C	
Humidity control	NO							
Power supply	230/1/50+N							
Defrosting	GAS CALDO							
Grids supplied	3				6			
Weight (Kg)	130				290			
dbA	49		58		53		61	
Absorbed Power (kW)	0,2		0,55		0,4		0,77	
Absorption (A)	1,1		3,2		2,4		5,5	
Refrigerating Power (kW)	0,44		0,57		0,55		0,82	

