

LEAVENING STOP CABINETS



FEATURES

- Stainless steel structure with external finish in scotch-brite satin or PPS with internal surfaces in aluminium
- Isolated with 75mm of high density polyurethane foam (40kg/m³)
- Indirect and uniform internal air circulation
- Automatic and uniformly controlled humidification and dehumidification system
- Electronic control by means of an LCD display with advanced features
- Adjustable feet in plastic/stainless steel (h120-150)
- Rounded internal corners to facilitate cleaning
- Moulded interior bottom with washing hole
- Electrical automatic defrosting
- Evacuation condensed in water network
- Refrigeration unit adapted for use in tropical conditions (high performance in environments up to 43°C)

	CSM FLP 6040	CSM FLP 6040	CSM FLP 6080	CSM FLP 6080
Number of doors	1			
Width (mm)	770		790	
Depth (mm)	822		1012	
Height (mm)	2025			
Temperature range	-3° C / +35° C	-20° C / +35° C	-3° C / +35° C	-20° C / +35° C
Humidity control	YES			
Power supply	230/1/50+N			
Defrosting	ELECTRICAL			
Number of pairs of tray guides	20			
Weight (Kg)	140	150		160
dbA	53	56	53	61
Absorbed Power (kW)	1,34	1,34	1,34	1,34
Absorption (A)	6,1	6,8	6,1	6,7
Refrigerating Power (kW)	0,55	0,43	0,55	0,61
Vaporization power (kW)	0,6	0,6	0,6	0,6
Heating power (kW)	0,6	0,6	0,7	0,7

