

TV SYNT 206



- N° 1 steam generator for each deck
- Deck ready for installation of supplementary steam generator
- Hood with exhaust fan
- Double speed exhausting hood
- (standard for width 186 - 234 - 248)
- Safety thermostat.
- Steam generators control by electrovalve with timer (SIMPLE excluded)
- Baking plates in "armored concrete".
- Motorised chimney shutter(excluding SIMPLE)
- Doors with low emission dismountable glass
- Automatic start (excluding SIMPLE)
- Baking timer (excluding SIMPLE)

<i>Power inlet</i>	400/3N~/50
<i>Water inlet</i>	Ø ½" GAS
<i>Steamer drain</i>	Ø 1" GAS
<i>Fuel pipe inlet</i>	-----
<i>Steam exhaust pipe</i>	Ø 250 mm*
<i>Fume exhaust pipe</i>	Ø 200 mm
<i>Frontal door (anti-explosion and clearing access)</i>	Pos.1
<i>Right door for furnace (optional)</i>	Pos.2
<i>Cleaning access door (optional)</i>	Pos.3

* Minimum diameter pipe exhaust fumes 200 mm.

	Chambers	Baking Surface	Dim.	Useful dimension chambers						Installed power		Minimum door width	Weight
				Length	Height					Thermic	Electrical		
	n°	m²	B mm	P mm	1°mm	2°mm	3°mm	4°mm	5°mm	kcal/h	kW	mm	kg
6,3 / 124x170-3	3	6,3	2430	1700	200	200	250	-	-	48.000		650x1850	3.250
8,4 / 124x170-4	4	8,4	2430	1700	200	200	200	250	-	56.000		650x2000	3.700
10,5 / 124x170-5	5	10,5	2430	1700	170	170	170	170	250	60.000		650x2100	4.150
8,0 / 124x214-3	3	8,0	2870	2140	200	200	250	-	-	56.000		650x1850	3.750
10,6 / 124x214-4	4	10,6	2870	2140	200	200	200	250	-	60.000		650x2000	4.350
13,3 / 124x214-5	5	13,3	2870	2140	170	170	170	170	250	70.000	1,0	650x2100	4.950
9,6 / 124x258-3	3	9,6	3310	2580	200	200	250	-	-	60.000		650x1850	4.250
12,8 / 124x258-4	4	12,8	3310	2580	200	200	200	250	-	70.000		650x2000	4.900
16,0 / 124x258-5	5	16,0	3310	2580	170	170	170	170	250	75.000		650x2100	5.550
8,0 / 156x170-3	3	8,0	2430	1700	200	200	250	-	-	56.000		650x1850	3.650
10,6 / 156x170-4	4	10,6	2430	1700	200	200	200	250	-	65.000		650x2000	4.200
13,3 / 156x170-5	5	13,3	2430	1700	170	170	170	170	250	70.000		650x2100	4.750
10,0 / 156x214-3	3	10,0	2870	2140	200	200	250	-	-	65.000		650x1850	4.250
13,5 / 156x214-4	4	13,5	2870	2140	200	200	200	250	-	75.000	1,0	650x2000	4.950
16,7 / 156x214-5	5	16,7	2870	2140	170	170	170	170	250	80.000		650x2100	5.650
12,0 / 156x258-3	3	12,0	3310	2580	200	200	250	-	-	70.000		650x1850	4.850
16,0 / 156x258-4	4	16,0	3310	2580	200	200	200	250	-	80.000		650x2000	5.650
20,0 / 156x258-5	5	20,0	3310	2580	170	170	170	170	250	90.000		650x2100	6.050
9,4 / 186x170-3	3	9,4	2430	1700	200	200	250	-	-	60.000		650x1850	4.050
12,5 / 186x170-4	4	12,5	2430	1700	200	200	200	250	-	70.000		650x2000	4.650
15,8 / 186x170-5	5	15,8	2430	1700	170	170	170	170	250	78.000		650x2100	5.250
12,0 / 186x214-3	3	12,0	2870	2140	200	200	250	-	-	70.000		650x1850	4.750
16,0 / 186x214-4	4	16,0	2870	2140	200	200	200	250	-	78.000	1,2	650x2000	5.550
20,0 / 186x214-5	5	20,0	2870	2140	170	170	170	170	250	90.000		650x2100	6.350
14,0 / 186x258-3	3	14,0	3310	2580	200	200	250	-	-	78.000		650x1850	5.450
19,0 / 186x258-4	4	19,0	3310	2580	200	200	200	250	-	87.000		650x2000	6.350
24,0 / 186x258-5	5	24,0	3310	2580	170	170	170	170	250	98.000		650x2100	7.250
12,6 / 248x170-3	3	12,6	2430	1700	200	200	250	-	-	70.000		650x1850	4.850
16,8 / 248x170-4	4	16,8	2430	1700	200	200	200	250	-	80.000		650x2000	5.600
16,0 / 248x214-3	3	16,0	2870	2140	200	200	250	-	-	78.000		650x1850	5.750
21,2 / 248x214-4	4	21,2	2870	2140	200	200	200	250	-	98.000	1,2	650x2000	6.750
19,2 / 248x258-3	3	19,2	3310	2580	200	200	250	-	-	90.000		650x1850	6.650
25,6 / 248x258-4	4	25,6	3310	2580	200	200	200	250	-	105.000		650x2000	7.800

